

# **PROWLER IIK**

## **Light Tactical All Terrain Vehicle**

### **Specifications \***

<b>Power Plant</b>	: 750 cc DFI 4 Valve 90 degree V-Twin, Liquid Cooled, Electric Start
<b>Power Train</b>	: Fully Automatic Transmission with HI/Lo Range, Reverse and Park (Limited Slip 4WD, 4WD Diff Lock, 2WD)
<b>Construction</b>	: Sealed Tubular Steel Structure, Chromalloy ROPS and Cargo Racks, Full Coverage Skid Plate System with No Removable Access Required for Vehicle Service or Maintenance
<b>Operation</b>	: Standard Automotive Driver Controls with Sealed Rack and Pinion Steering, Console Mounted Switch Selectable Dual Range Drive
<b>Top Speed</b>	: 50 mph (4WD, Hi Range)
<b>Instrumentation</b>	: Digital Multifunction Display with LCD Speedometer / Odometer, Dual Trip Meters, Hour Meter and Clock, Fuel Gage, Warning Lights and Drive Train Position Indicators
<b>Suspension</b>	: Front - Independent Double Wishbone A Arms, Adjustable Preload Gas Charged Shock Absorbers Rear - Independent Double Wishbone A Arms, Adjustable Preload Gas Charged Shock Absorbers
<b>Braking</b>	: Front - Dual Hydraulic Disc Rear - Sealed Multi Disc Full Engine Braking on all 4 Drive wheels
<b>Payload</b>	: 1400 lb
<b>Operator Safety</b>	: Roll Over Protection System (ROPS) Exceeds SAE J1524 and ISO Std 3471, Crew Seat Restraints SFI-16-1 certified
<b>Towing Capacity</b>	: 2550 lb (terrain dependent)
<b>Winch</b>	: 3000 lb, with Wireless Remote Control
<b>Tires / Wheels</b>	: EMT Run Flat / Double Reinforced Rim Wheels (all four wheels same size)
<b>Fuel Capacity</b>	: 7.4 gal. (with optional in-line 8 gal. spare tank)
<b>Ground Clearance</b>	: 12" (13" @ Approach and Departure)
<b>Wheel Base</b>	: 76"
<b>Track Width</b>	: 50" front, 50" rear (center to center)
<b>Overall Width</b>	: 58"
<b>Overall Length</b>	: 114"
<b>Height</b>	: 68" (with convertible ROPS, 60")
<b>Weight</b>	: (dry) 1250 lb
<b>Ford Depth</b>	: 30"